



CANON ImageRUNNER 3235i

Main Unit Specs

Type	Monochrome Digital Multifunction Imaging System
Imaging System	Laser Dry Electrostatic Transfer
Developing System	Dry Monocomponent Toner Projection
Fixing System	RAPID Fusing System
Image Server Memory	1GB RAM+ 256MB RAM Max. Memory: 1GB RAM+ 768MB RAM Hard Disk Drive: 60GB
Max Mailboxes Supported	100 User Inboxes, One Memory RX Inbox, 50 Confidential Fax Inboxes Scan Features Network TWAIN Scan: Standard Network Scan Utility: Color Network ScanGear
Max Copy Reservation	10 Jobs
Scanning Resolution	600 x 600 dpi Copy Resolution: 1200 x 600 dpi (Interpolated)
Printing Resolution	1200 x 1200 dpi•
Halftone	256 Gradations of Gray
Letter	Up to 35 ppm
First Copy Time	3.9 Seconds (From Platen Glass) 5.9 Seconds (From DADF)
Multiple Copies	1 - 999
Magnification	Platen: 25% - 400% (in 1% Increments) DADF: 25% - 200% (in 1% Increments)
Preset Reductions	25%, 50%, 64%, 73%, 78%
Preset Enlargements	121%, 129%, 200%, 400%

Acceptable Originals	Sheets, Books, and 3-Dimensional Sheets, Books, and 3-Dimensional Acceptable Paper Sizes: 11 x 17, Legal, Letter, Letter-R
Maximum Original Size	11 x 17 Min. Copy Size: 3-7/8 x 5-7/8 (Stack Bypass)
Standard Paper Capacity	Dual 550-Sheet Paper Cassettes + 50-Sheet Stack Bypass Optional: Dual 550-Sheet Paper Cassettes + 2,700-Sheet Paper Deck
Manual Bypass	50-Sheet Stack Bypass
Maximum Paper Capacity	4,950 Sheets

Output Sizes

Cassette	Upper Cassette: Legal, Letter, Letter-R, Statement-R, Executive Lower Cassette: 11 x 17, Legal, Letter, Letter-R, Statement-R, Executive
Bypass	11 x 17, Legal, Letter, Letter-R, Statement-R, Executive, Free Size (3-7/8 x 5-7/8 to 11-5/8 x 17), and Envelopes

Acceptable Paper Weights

Cassette	17 lb. to 20 lb. Bond
Bypass	17 lb. to 24 lb. Bond
Duplexing	Standard Automatic Trayless Duplexing
Warm Up Time	10 Seconds or Less From Sleep Mode 35 Seconds or Less From Main Power Off Network Interface Connections: 10/100/1000 Base-TX (RJ-45), USB 2.0 (Device), USB 2.0 (Host) x 2
Exposure Control	Automatic or Manual (9 Levels)
Power Requirements	120V AC, 60Hz, 10A Power Consumption: 1.41kW (Max.) Plug: NEMA 5-15P
Dimension	35-1/2 x 22-1/4 x 27-5/8 (901mm x 565mm x 700mm)
Weight	181 lb. (82kg)

Supplies

Weight	24,000 Impressions at 6% Image Coverage
--------	---

Accessories

Feeders

Description	Duplexing Automatic Document Feeder
Acceptable Originals	Statement to 11 x 17
Capacity	100 Sheets (20 lb. Bond)
Paper Weights	One-Sided Scanning: 11 lb. to 32 lb. Bond Two-Sided Scanning: 13 lb. to 32 lb. Bond USB Memory Media Supported Applications: Scan to USB Memory Media, Print from USB Memory Media Supported Print File Formats: TIFF, JPEG, PDF Supported Scan File Formats: TIFF, JPEG, PDF, PDF (Compact), ** TIFF, JPEG, PDF, PDF (Compact), ** TIFF, JPEG, PDF, PDF (Compact), ** Digital Device Signature PDF, *** Digital Device Signature PDF, *** ♦ Required Accessories USB Memory Connectivity Kit-A1
Description	Cassette Feeding Unit-Y3 (Opt.)
Acceptable Originals	11 x 17, Legal, Letter, Letter-R, Statement-R, Executive
Capacity	Dual 550-Sheet Cassettes (1,100 Sheets at 20 lb. Bond)
Paper Weights	Approx. 50.7 lb

Paper Supply Options

Description	Paper Deck-Q1 (Opt.)
Paper Capacity	2,700 Sheets (20 lb. Bond)
Paper Sizes	Letter
Paper Weights	17 lb. to 24 lb. Bond
Dimensions	18-5/8 x 14-5/8 x 23-1/4
Weight	Approx. 65.3 lb.
Description	Inner 2-Way Tray-D1 (Opt.)
Number Of Cassettes	Two

Paper Capacity	Upper Tray: 100 Sheets (LTR), 50 Sheets (Other Sizes) Lower Tray: 250 Sheets (LTR), 100 Sheets (Other Sizes)
Paper Sizes	11 x 17, Legal, Letter, Letter-R, Statement-R, Executive, Envelope, Freesize (3-7/8 x 5-7/8 to 11-3/4 x 17)
Paper Weights	17 lb. to 32 lb. Bond Attachable Accessories: Copy Tray-J1

Output Options

Finishers Output Trays

Description	Finisher-S1 (Opt.)
Paper Weights	17 lb. to 32 lb. Bond
Paper Size	11 x 17, Legal, Letter, Letter-R, Statement-R, Executive, Envelope, Freesize (3-7/8 x 5-7/8 to 11-3/4 x 17)
Number Of Trays	One (Second Tray Optional)
Top Tray	Non-collate, Collate, Group Mode: 1,000 Sheets (Letter, Statement-R) 500 Sheets (11 x 17, Legal, Letter-R) Staple Mode: 1,000 Sheets/30 Sets (Letter) 500 Sheets/30 Sets (11 x 17, Legal, Letter-R)Tray Capacity (with Additional Finisher Tray-B1) Non-collate, Collate, Group Mode: 300 Sheets Per Tray (Letter, Statement-R), 150 Sheets Per Tray (11 x 17, Legal, Letter-R) Staple Mode: 300 Sheets/30 Sets Per Tray (Letter), 150 Sheets/30 Sets Per Tray (11 x 17, Legal, Letter-R)
Staple Capacity	50 Sheets (Letter), 30 Sheets (11 x 17, Legal, Letter-R)
Staple Positions	Top Left Corner: 11 x 17 (Landscape), Legal (Landscape), Letter, Letter-R Top Right Corner: 11 x 17 (Portrait), Legal (Portrait)Attachable Accessories: Additional Finisher Tray-B1, Puncher Unit-R1, Copy Tray-J1Puncher Unit-R1 (Option for Finisher-S1) Acceptable Paper Sizes: 11 x 17, Legal, Letter, Letter-R Acceptable Paper Weight: 17 lb. to 32 lb. Bond

	Punch Type Two Holes: Legal, Letter-R Three Holes: 11 x 17", Letter Punch Waste Capacity Two Holes: Approx. 2,500 Sheets Three Holes: Approx. 1,500 Sheets
Description	Finisher-AE1/Saddle Finisher-AE2 (Opt.)
Paper Weights	17 lb. to 32 lb. Bond
Paper Size	11 x 17, Legal, Letter, Letter-R, Statement, Statement-R, Executive, Statement, Statement-R, Executive, to 11-3/4 x 17)
Number Of Trays	2 Trays
Top Tray	Non-collate, Collate, Group Mode: 1,000 Sheets (Letter, Statement-R, Executive), 500 Sheets (11 x 17, Legal, Letter-R) Staple Mode: 1,000 Sheets/30 Sets (Letter, Executive), 500 Sheets/30 Sets (11 x 17, Legal, Letter-R)
Staple Capacity	50 Sheets (Letter, Executive), 30 Sheets (11 x 17, Legal, Letter-R)
Staple Positions	Corner Staple, Double-Staple
Paper Sizes	11 x 17, Legal, Letter-R Saddle-Stitch Capacity: 15 Sheets (60-Page Booklets) Tray Capacity: 25 Sets (1 to 5 Sheets), 15 Sets (6 to 10 Sheets), 10 Sets (11 to 15 Sheets) Folding: V-Folding*
Dimensions	Finisher-AE1: 40-7/8 x 25-3/8 x 25-7/8 Saddle Finisher-AE2: 40-7/8 x 29-3/8 x 25-7/8 Attachable Accessories: Puncher Unit-M1Puncher Unit-M1 (Option for Finisher-AE1/Saddle Finisher-AE2) Acceptable Paper Sizes: 11 x 17, Legal, Letter, Letter-R Acceptable Paper Weight: 17 lb. to 32 lb. Bond Punch Type Two Holes: Legal, Letter-R Three Holes: 11 x 17, Letter Punch Waste Capacity: Approx. 3,000 Sheets
Fax Board	

Description	Super G3 Fax Board (Opt.)
Applicable Line	Public Switched Telephone Network (PSTN) Connection Lines: Up to 3 Sending/Original Size: Statement to 11 x 17 Receiving/Printing Size: Statement to 11 x 17

Print Board

Processor	Canon Custom Processor
Standard Memory	1GB RAM+ 256MB RAM(Shared)
Maximum Memory	1GB RAM+ 768MB RAM(Shared)
Hard Disk	60GB (Shared)Maximum Print Resolution: 1200 x 1200 dpi•
PDL Support	Std. UFR II, PCL 5e/6, PS 3 em.
Print Controller Technology	UFR II: Windows® 2000/XP/Server 2003/Windows Vista®, Citrix MetaFrame, Macintosh® OS X (OS 10.2.8 or later) PCL 5e/6: Windows 2000/XP/Server 2003/Windows Vista, Citrix MetaFrame PS 3 em.: Windows 2000/XP/Server 2003/Windows Vista, Citrix MetaFrame, Macintosh OS X (OS 10.3.8 or later)

Description	PCL Printer Kit-AA1
PDL Support	PCL 5e, PCL 6 Internal Fonts: 80 Scalable Fonts, 30 Barcode, 10 Bitmap, 2 OCR Fonts Supported OS: Windows 2000/XP/Server 2003/Windows Vista, Citrix MetaFrame

Description	Citrix MetaFrame ◆ ◆
PDL Support	PostScript 3 Emulation Internal Fonts: 136 Scalable Fonts Supported OS: Windows 2000/XP/Server 2003/Windows Vista, Citrix MetaFrame, Macintosh OS X (OS 10.3.8 or later)

Send Expansion Sets

Description	Color Universal Send Features (Std)
Sending Method	E-mail, I-fax, SMB, File Server (FTP, IPX, WebDAV), User Inbox, Super G3 Fax (Optional)

Address Book Capacity

Max. 1,800 Destinations (Includes 200 One-Touch Buttons)

Max. 5 LDAP Servers Color Mode: Auto Color Select (Full Color/Grayscale)

Auto Color Select (Full Color, B/W)

Full Color Grayscale, B/W Communication Protocol

File: FTP (TCP/IP), SMB (TCP/IP), NCP (IPX), WebDAV

E-mail/I-fax: SMTP, POP3, I-fax (Simple, Full)Data Format

File, E-mail: TIFF, JPEG, PDF, XPS, PDF/XPS (Compact),** PDF/XPS (Trace & Smooth),**

PDF/XPS (OCR),** Encrypted PDF,*** Digital

Device Signature PDF/XPS,*** Digital User

Signature PDF/XPS ◆ OTHER OPTIONAL

ACCESSORIES

Cabinet-P1FL Cassette-Y1(replacement)FL

Cassette-Z1 (replacement)Envelope Feeder

Attachment-C2Copy Tray-J1Document Tray-J1Card

Reader-C1Carder Reader Kit-B3PCL Printer Kit-

AA1°PS Printer Kit-AA1°Direct Print Kit-F1°Direct

Print Kit-F1 ◆ ◆ Encrypted Secure Print Software-

C1 ◆ ◆ Color Universal Send Kit-P1°Universal

Send Advanced Feature Set-B1†††°Universal Send

Security Universal Send Security†††°Digital User

Signature Kit-B1eCopy Suite Web Access Software-

G1†USB Memory Connectivity Kit-A1Secure

Watermark-A1Super G3 Fax Board-AC1Super G3

2nd Line Fax Board-AC1Super G3 2nd/ 3rd Line Fax

Board-AC1Board-AC1 (512MB)°System Upgrade

RAM-A1Access Management System Kit-A2HDD

Data Encryption Kit-B5HDD Data Erase Kit-

B2Braille Label Kit-E1ADF Access Handle-A1Voice

Operation Kit-B1††Voice Guidance Kit-D1Remote

Operator's Software Kit-A3Workflow Composer-

C1Workflow Composer-C1Expansion Bus Board-

E1Wireless LAN Board-A1IP Sec Board-

A1Removable Hard Disk Drive Kit-C1• 1200x1200

dpi printing resolution is not available with PCL5e.

* Available with Saddle Finisher-AE2 only.

** Requires Universal Send Advanced Features Set-B1 (Standard on 3245i/3235i).

*** Requires Universal Send Security Feature Set-B1 (Standard on 3245i/3235i).

◆ Requires Digital User Signature Kit-A1.

◆ ◆ Requires PCL Printer Kit-AA1.

† Requires Additional Memory Type A to display

Web Flash content. Requires the PS Printer Kit-AA1 or Direct Print Kit-F1 if printing PDF files.

†† Requires Additional Memory Type A.

††† Requires Color Universal Send Kit-P1 or USB Memory Connectivity Kit-A1.

º Standard with imageRUNNER 3245i/3235i models.

LANDER COPY DIGITAL

Av. Gil Fortoul entre calles Simón Planas y Reynaldo Hahn, Quinta Módulo GB. Urbanización Santa Mónica. Caracas – Venezuela

Teléfono: 0212 417 12 88

E-mail: info@landercopy.com

www.landercopy.com

